



### PRODUCT FEATURES

<b>NO. OF LAMPS IN FIXTURE:</b> 1-4	<b>LIGHT OUTPUT:</b> 750 Lumen	<b>BATTERY:</b> NiCD
<b>INPUT VOLTS:</b> 120/277V, 60Hz	<b>ILLUMINATION TIME:</b> 90 Minutes	<b>WARRANTY:</b> 5 Years

### ILLUMINATION

- Works with or without an AC ballast to convert new or existing fluorescent fixtures into unobtrusive emergency lighting.
- Operates one or two lamps in the emergency mode for a minimum of 90 minutes.
- Provides a maximum initial lumen output of 750 lumens.

### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- Long-life, maintenance-free, rechargeable sealed NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to fluorescent lamp(s) for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### MOUNTING

- Suitable for installation inside, on top, or in remote of the fixture.
- Can be used in both switched and unswitched fixtures.
- UL listed for factory or field installation.

### HOUSING

- Durable painted steel construction in white finish.
- Provided with 2' flex conduits on both ends.
- Compact design fits most fluorescent fixtures.

### WARRANTY


- Five year warranty against defects in material and workmanship. (Lamps excluded.)
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.
- UL listed for damp locations.

### LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates one 17W-40W T8 through T12, two 13W-39W, one 13-42W 4-pin compact, or one 18W-40W 4-pin long compact fluorescent lamps.

### PHYSICAL SPECIFICATIONS

#### CASE DIMENSIONS



<b>LENGTH</b>	9.50"
<b>WIDTH</b>	2.40"
<b>HEIGHT</b>	1.50"

**CASE MATERIAL:** Steel

When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.

### INITIAL LUMEN OUTPUT

LAMP	INITIAL LUMENS	
	1-Lamp	2-Lamp
4-Pin PL CF 13W	350	425
4-Pin PL CF 18W	400	550
4-Pin PL CF 26W	475	650
4-Pin PL CF 32W	600	750
4-Pin PL CF 42W	750	–
4-Pin Long CF 18W	550	–
4-Pin Long CF 24W	600	–
4-Pin Long CF 36W	650	–

NOTE: In 2-lamp operation, lumens are equally split between the two lamps.