



KT-EMRG-800-T5

EMERGENCY BALLAST



PRODUCT FEATURES

NO. OF LAMPS IN FIXTURE: 1-4	LIGHT OUTPUT: 800 Lumen	BATTERY: 6V Sealed NiCD
INPUT VOLTS: 120/277V, 60Hz	ILLUMINATION TIME: 90 Minutes	WARRANTY: 5 Years

OPERATING DETAILS

- For use in new or existing fixtures, with or without an AC ballast, where emergency lighting is needed.
- Operates one lamp in the emergency mode.
- 2-in-1 LED indicator light and push-to-test switch (for mandated code compliance testing).
- Internal battery automatically connects to the fluorescent lamp for minimum 90 minute emergency illumination via an internal solid-state transfer switch.
- A discharged battery completely recharges in 24 hours, via a fully automatic solid-state, two-rate charger.
- AC output helps to guarantee compatibility with new lamp technologies.
- Features Time Delay Technology which helps to overcome end-of-life circuit protection.

LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates the following lamps under emergency power:

	T5 (W)	T8 (W)	T10 (W)	T12 (W)	4-Pin CFL (W)	4-Pin Long CFL (W)	T9 Circline (W)
No. of Lamps	1	1	1	1	1	1	1
Wattage	8-28	17-40	17-40	17-40	13-26	18-50	20-40

INITIAL LUMEN OUTPUT


LAMP TYPE	INITIAL LUMENS	LAMP TYPE	INITIAL LUMENS
	1-Lamp		1-Lamp
T5 14W	450	4-Pin PL CF 13W	425
T5 21W	500	4-Pin PL CF 18W	575
T5 28W	750	4-Pin PL CF 26W	625
T5HO 54W	800	4-Pin Long CF 18W	550
T8 17W	650	4-Pin Long CF 24W	625
T8 32W	700	4-Pin Long CF 36W	675
T12 20W	625	4-Pin Long CF 40W	675
T12 40W	700	4-Pin Long CF 50W	725

KT-EMRG-800-T5

EMERGENCY BALLAST

PHYSICAL SPECIFICATIONS

CASE DIMENSIONS



LENGTH	17.60"
WIDTH	1.28"
HEIGHT	1.19"
CASE MATERIAL: Galvanized Steel (Low Profile Design)	

MOUNTING

- UL listed for factory or field installation. Suitable for damp location.
- Can be mounted inside, on top, or remote from the fixture.*
- Designed to be used in both switched and unswitched fixtures.

* When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-EMRG-800-T5-DP	Distributor Pack	1	Quick Ship

CATALOG NUMBER BREAKDOWN

KT-EMRG-800-T5-DP

Keystone Technologies	Emergency Ballast	800 Lumen	T5 Applications	Packaging Style
-----------------------	-------------------	-----------	-----------------	-----------------

Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.