



Catalog Number	
Notes	Type

## FEATURES AND SPECIFICATIONS

### APPLICATIONS:

- For luminaires where lights are to be on continuously (shorting cap) or left off (open cap)

### DESIGN DETAILS

- MOV Rated for 265Joule/6000 Amp (shorting cap only)
- Neoprene Base Gasket has a continuous use temperature of 105°C
- Polypropylene Cover
- Brass Legs

### REGULATORY LISTINGS

- Exceeds ANSI C136.10-1996


### OPERATING CHARACTERISTICS

- Voltage 105 to 530 VAC, 50/60Hz
- -40 to +70°C ambient

### Locking Type Accessory

# CAP Series

## Shorting and Open



## ORDERING LOGIC

Example: DSHORT VBK J50

Series
--------

- DSHORT** Shorting Cap,  
Continuously On
- DOPEN** Open Cap,  
Continuously Off

Surge Protection
------------------

- SBK** Shorting Cap, Black cover
- VBK** Shorting Cap, 265J MOV, Black cover
- SRD** SRD Open Cap, Red cover

Pkg. Qty.
-----------

- J12** 12 Units
- J50** 50 Units



Expanding the boundaries of lighting™

### Sheet # DTL-CAP-B

Six Year Warranty: The CAP series controls are warranted to be free of manufacturing quality defects for a period of (6) years from the date of sale.